



SLACK ADJUSTERS

CHAPTER 9

OE5019LH

SPLINE

1 1/4" x 10

Details

4 1/2", 5 1/2" Hole Spacing, 1/2" Clevis Pin Hole, Offset Arm

APPLICATION

Front Steer Axles
Left Hand

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating



OE5019RH

SPLINE

1 1/4" x 10

Details

4 1/2", 5 1/2" Hole Spacing, 1/2" Clevis Pin Hole, Offset Arm

APPLICATION

Front Steer Axles
Right Hand

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating



OE5020

SPLINE

1 1/2" x 10

Details

5", 6", 7" Hole spacing, 1/2" Clevis pin hole, straight arm

APPLICATION

General purpose truck and trailer
12 1/4", 16 1/4", & 18" Brakes

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating



OE5020HD

SPLINE

1 1/2" x 10

Details

5", 6", 7" Hole spacing, 1/2" Clevis pin hole, straight arm

APPLICATION

General purpose truck and trailer
12 1/4", 16 1/4", & 18" Brakes

COMMENTS

Heavy Duty Version of OE5020
Has 3/4" Adjuster Nut





SLACK ADJUSTERS

CHAPTER 9

OE5021

SPLINE

1 37/64" x 37

Details

6" Hole spacing, 1/2" Clevis pin hole, straight arm

APPLICATION

Propar 12 1/4" & 16 1/2" Brakes

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating



OE5022

SPLINE

38mm x 10

Details

120, 150, 180, 220, 250mm hole spacing, 14mm Clevis Pin hole, straight arm

APPLICATION

B.P.W. Early & New Generation Axles

COMMENTS

Standard 22000lb torque rating



OE5023

SPLINE

1 1/2" x 10

Details

5 1/2", 6 1/2" Hole spacing, 1/2" Clevis pin hole, straight arm

APPLICATION

General purpose truck and trailer

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating



OE5024

SPLINE

1 1/2" x 28

Details

5 1/2", 6 1/2" Hole spacing, 1/2" Clevis pin hole, straight arm

APPLICATION

General purpose truck and trailer, 12 1/4" & 16 1/2" Brakes with 28 spline shafts

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating





SLACK ADJUSTERS

CHAPTER 9

OE5025



SPLINE

1 1/2" x 28

Details

5", 6", 7" Hole spacing, 1/2" Clevis pin hole, straight arm

APPLICATION

General purpose truck and trailer with 28 spline shafts

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating

OE5026LH



SPLINE

1 1/2" x 10

Details

4", 5", 6" Hole Spacing, 1/2" Clevis Pin Hole, Offset Arm

APPLICATION

Various Front Axles
Left Hand

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating

OE5026RH



SPLINE

1 1/2" x 10

Details

4", 5", 6" Hole Spacing, 1/2" Clevis Pin Hole, Offset Arm

APPLICATION

Various Front Axles
Right Hand

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating

OE5028



SPLINE

1 1/2" x 10

Details

6" Hole spacing, 1/2" Clevis pin hole, Curved arm

APPLICATION

Spicer & Standard Forge Low Bed Trailers, 12 1/4" Brakes Heavy
Duty Air Chamber Brackets should be used

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating



SLACK ADJUSTERS

CHAPTER 9

OE5029LH

SPLINE

1 1/2" x 10

Details

5", 6" Hole Spacing, 1/2" Clevis Pin Hole, Offset Arm

APPLICATION

BPW & Various European Drive Axles
Left Hand

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating



OE5029RH

SPLINE

1 1/2" x 10

Details

5", 6" Hole Spacing, 1/2" Clevis Pin Hole, Offset Arm

APPLICATION

BPW & Various European Drive Axles
Right Hand

COMMENTS

Remove bushing for 5/8" clevis pin hole
Standard 22000lb torque rating

